Material Instructions

MasterJet



Please make sure the surface is smooth and solid before attaching your picture. Low adhesion of two components (e.g. wall paint or plaster) can cause problems. To ensure the glue's durability, the surface also has to be **dry and free of dust/grease** (please clean the surface).

The following surfaces are suitable for your picture:

- · walls made of wood, plastic and veneer
- · floors made of stone and wood
- windows and doors made of glass, wood and veneer
- metals and lacquers
- ordinary and woodchip wallpaper, painted and plastered walls

Our material can be used several times.

Plasticizer

Some colors and materials contain admixtures like latex or silicone. These can influence the effect of the glue. To avoid possible problems, we recommend to make a test on the selected surface.

Storage

If you wish to reuse our polyester material, you have to use an **intermediate layer** for it. That means, the glue must **not** come into contact with the printed side.

Scratches

The printed side must **not** come into contact with sharp objects (fingernails, rings, objects with sharp edges and so on).

Adhesive window design

For thermal and glass technology reasons the fabric only should be applied on flat glass in the interior or permanently shaded facades.

Geschäftsführer: Jens Hermsmeier

Fon: (+49) 5207 99 37 116 Fax: (+49) 5207 99 37 119 Mail: info@postertex.de Web: www.postertex.de (www.wtfe.de) Postertex GmbH Sparkasse Bielefeld BLZ: 480 501 61 IBAN: DE21 4805 0161 0044 1901 97 BIC: SPBIDE3BXXX